

700 King, the King of Overlock Machines



銀箭牌 全新力作 包缝之王,<mark>700 KING!</mark>

唯有"干"者,方足以傲视群雄!

700K SERIES

超高速直针式针棒包缝机

Ultra high speed direct type needle bar overlock safety stitch machine.



Direct Drive



747 k

线数 ↓
Thread numbers

机种别 Machine type

700K

超高速直针式针棒包缝机 Ultra high speed direct type needle bar overlock safety stitch machine.

700KD

直驱式超高速直针式针棒 包缝机

Direct drive ultra high speed direct type needle bar overlock safety stitch machine.

降低噪音不占空间,并节约40%的电力,大幅提升工作效率

Reduces noise, occupies less space, and saves the power up to 40%, it will improve the work efficiency greatly. 514

缝合方式

Sewing types

503

504

512

515

515

516

514 + 401

Presser foot type

车缝布料

M

Sewing material

F: 轻薄布料 Fine weight material

L: 薄布料 Light weight material

M:中厚布料 Medium weight material

H:厚布 Heavy weight material 2

4

VT

配件 Attachment



needle gauge

包边宽度 Seam width

CHARACTERISTICS

SiRUBA®

选配件 Optional device



LED灯

具有高亮度、超省电之 LED照明装置,体贴使 用者在穿线及目视线迹 之方便性

LED device with high illumination and power save. Give convenience of threading and observing stitches.

独特的设计 Unique design



强制滤油装置

独特之强制滤油与自动 润滑装置

Automatically oiling system with filter pump.



针棒吸油

为防止重要的缝制品沾染污油,增加一回油系统抽取润滑过程中因牵引带出来的油渍。

To prevent from being polluted by the oil sludge, an oil recycle system is added to clean the oil sludge from lubrication.



收线机构

车缝不同布料时,相对改变线的松紧度,微调的收线机构,使缝制品的品质能达到完美。

For different materials, changing the tensions as well. A mechanism for you to do micro adjustment of thread contraction, and improve the quality to perfection.



过线机构

可调整及刻划的设计,轻 松完成下勾针前後移动 与双链缝勾针前後移动 的精确调整

An adjustable design for you to accomplish accurate adjustments in back and forth movements of the lower looper and the looper of double chainstitch.



针棒供油

本机种采全密封式设计, 针棒供油系统采取直接 给油方式。

An entirely sealed machine with direct oiling solution to oiling system.

Directly oiling the needle bar system.



送具防油

在机构增加多层的防油机构达到完全阻油的目的,送具不会因需润滑而将油带出机器外。 Multi-layer oil proof mechanism outside the device can isolate the oil. The feed dog will no longer take the oil out during lubrication.



底部回油装置

针棒机构采循环式强制 润滑设计,采取油泵强制 真空回油,解决渗油问 题。

Actively cycling lubrication of needle bar. Oil vacuum discharge pump. Solve the oil leaking!









700K SERIES

超高速直针式针棒包缝机 Ultra high speed direct type needle bar overlock safety stitch machine.

MODEL	х	•	→ ₩ ←	# + mm		WW	###	mm -	Needle No.	10
737K-504M2-04	1	3	-	4	-	0.7-2	3.8	5.5	#11	7500
737K-504M3-05	1	3	-	5	-	0.7-2	3.8	5.5	#11	7500
747K-512M1-25	2	4	2	5	7	0.7-2	3.8	6.0	#11	7500
747K-514M2-24	2	4	2	4	6	0.7-2	3.8	6.0	#11	7500
757K-516L1-24	2	5	2	4	6	0.7-2	3.8	6.0	#14	7500
757K-516L1-35	2	5	3	5	8	0.7-2	3.8	5.5	#14	7500
757K-516M2-35	2	5	3	5	8	0.7-2	3.8	5.5	#14	7500
757K-516M2-55	2	5	5	5	10	0.7-2	3.8	6.0	#14	7500
767K-516M2-324	3	6	3 X 2	4	9	0.7-2	3.8	6.0	#11	7000
767K-516M2-524	3	6	5 X 2	4	11	0.7-2	3.8	6.0	#11	7000



高林股份有限公司 KAULIN MFG. CO., LTD.











The specification and/or appearences of the equipment described in this catalogue are subject to change without previous notice because of modification.