FW-740TA

曲臂式四針六線拼縫機(迷你伺服馬達)

SHING RAY

FOUR-NEEDLE AND SIX-THREAD FEED-OFF ARM MODEL INDUSTRIAL INTERLOCK SEWING MACHINE(MINI SERVO MOTOR)





選購件-AW吸布層裝置

本機特點 (Feature):

專業設計:超短型直驅小馬達及相接結構

小馬達設計車縫更靈敏、拆裝更方便、振動減少、噪音低。

It is the design of mini servo-motor to offer more sensitive, more convenient in assembly, less vibration and lower noise.

全新專利隱藏式抬壓腳

全新設計之隱藏式抬壓腳機構與機座創新結合在一起,美觀、遊振。 To combine hidden presser foot lifter and holder is newly design, beauty and anti-vibration.

超大操作空間設計

專利新款的創新機座設計,為車縫提供了超大的工作臺操作空間,更 利於大件物品的縫製,提高工作效率與縫製效果。

The innovative machine seat of the new style of the patent is designed, offer the work operation space oversize for the machine operates, benefit the sew of bulky res, enhance working efficiency and sew the result.

改良型密封式過線結構

防止繞線,使車縫的過線更為滑順。

To reduce the distance from thread stand to the machine and offer thread supply and tension smoother.

彈片式壓腳機構

該機構的作用,使内衣用薄布料及高彈性面料均能充分對應。

The design of the machine can handle thin underwear material and highly elastic material.

選購件-AW吸布屑裝置

改良型吸布屑裝置,加裝此選購件,可吸走切斷的布屑,使 車縫平順、線跡美觀。

The improved fabric chips suction device is an optional one which can suck in the fabric chips so as to smooth the stitching and beautify seam when it is equipped additionally on the







AK可調式4針6線拼縫機氣動切線裝置

ADJUSTABLE PNEUMATIC TYPE CHAIN CUTTER FOR FLATSEAMER









本機特點 (Feature):

氣動切線裝置

專利設計的氣動切線裝置,安裝容易、操作方便,可切線、切帶,提 升繼物質量、操作效率。

The patent pneumatic type chain cutter installs in easy and operates in convenience which could cut thread & tape to increase quality & efficiency of garment production.

内藏式進氣管

吸屑装置中專利的内藏式進氣管設計、進氣穩定、增強吸屑裝置的吸 力。

The patent designed invisible blower of suction device which offers a stable blowing and increases the power of suction device.

特殊滑軌傳動結構

氣壓缸專利的滑軌傳動結構,滑軌可反覆調整,延長使用壽命。 The patent sliding rail of cylinder is available to adjust repeatedly which could increase the operating life.

多向可調式轉接頭

多向可調式吸屑裝置轉接頭,可依客戶實際需求,調整 到最適當的角度。

Multi-Adjustable Suction Device Adapter which depends on customer demanded to adjust into precise angle.

電眼回饋位置

精心設計的電眼回饋位置,提供迅速、精準的作動。 The special designed feedback position of electric eye offers swift and precise motion.

微調式切刀組

微調式切刀組,可依使用狀況做出精細的調整。 Micro-adjustable cutter could follow the operation to adjust in precise.

SPECIFICATION:

Model	1		 	+ + 	<u>→</u> .+	OF T	1	1	(D)
FW740-TA	4	6	4.8	1.6~2.5		1:07-1:05	04/0>		4200
	4~5	5~7	5.2				01(8mm) 02(6mm)		
	4	6	6.0 6.4						
FW740-TA-S	4	6							
FW740-TA-T1			5.2				02(6mm)	30	
FW740-TA-T2			6.0				01(8mm)		
FW740-TA-DS			5.2 6.0 7.0 8.0				01(8mm)		
FW740-TA-R			2				02(6mm)		
FW740-TA-H			5.2						
FW740-TA-RH			6.0						